

6" Active Wall Mount Speaker (White in Pair, 2x25W)
Features

- Powered speaker with amplifier of stereo sound system
- Two way speaker system, 6" woofer and 1.5" tweeter
- Ideal for school, hospital, meeting room projector and laptop use
- First-level Hi-fi sound quality
- Input support laptop, Ipod, Iphone and microphones
- 25 watts stereo at 8ohms output
- Mounting bracket is supplied
- RS232 control port and remote control could be customized if order quantity is attractive, default specification not include this feature.


Description

The T-776AW is a 5" stereo loudspeaker set that consists of a passive loudspeaker and an active loudspeaker.

It is ideal choice for AV applications such as meeting room, multi-media class room for small presentations. The active loudspeaker package is designed with volume and tone controls, accurate clip indicators and built-in a stereo amplifiers. The rated power output is 20W at 8ohms system.

ABS cabinet, metal grille and metal mounting bracket are of black finish, the easy mounting bracket is supplied in the packaging.

Specification


Model	T-776AW (White)
RMS	25W x 2 @8Ω
Input Sensitivity	0.7V
Frequency Response	20Hz-20KHz/1W, ±0.5dB
THD	20Hz-20KHz/1W, 0.05%
Damping Factor	>200@8Ω/400Hz
Conversion Rate	30V/US
Channel Degree of Separation	>75dB
S.N. Ratio	>95dB
Amplifier	AB class
Indication	Power and channel signal
Protection	High temp, overload, short circuit and clip
Treble Control	±10dB
Bass Control	±10dB
Input Connector	Balanced phoenix connector, dual RCA and stereo 3.5mm earphone input
AC Power Supply	~220V-240V 50/60Hz
Dimensions	216x245x290mm
Weight	10.1Kg (per pair)

6" Active Wall Mount Speaker (White in Pair, 2×25W)

Appearance:



Direction Diagram:



Frequency Response:

