NAC-710W
Wall Speaker



2-Way Speaker | Wall-Mount Installation | 8Ω Low-Impedance Input | 70V/100V

INTRODUCTION

SPON Wall Speaker NAC-710W is an indoor wall-mounted speaker with clear sound performance, easy installation, and suitability for public areas, meeting rooms, and other indoor applications.

MAIN FEATURES

- **Two-Way Speaker Design:** Adopts a two-way speaker design with a 4" woofer and 1" silk tweeter for clear and balanced sound reproduction.
- **Flexible Input Options:** Supports 70 V / 100 V line input and 8 Ω low-impedance input for flexible system integration.
- **Wide Sound Coverage:** Features a 115° coverage angle, making it suitable for indoor paging and background music applications.

PARAMETERS:

Frequency Response	110 Hz to 20 kHz
Sensitivity	84 dB ± 3 dB (1 m / 1 W)
Max. SPL	97 dB (1 m / 20 W)
Rated Power	20 W
Power Taps (100 V)	20 W / 10 W / 5 W / 2.5 W
Power Taps (70 V)	20 W / 10 W / 5 W / 2.5 W / 1.25 W
Low-Impedance Input	8 Ω
Input Voltage	70 V / 100 V
Speaker Design	Two-way speaker
Speaker Component	4" woofer + 1" silk tweeter
Coverage Angle	115°
Housing Material	HIPS
Grille Material	Powder-coated iron mesh
Color	Black
Mounting	Wall-mounted
Application Environment	Indoor
Operating Temperature	-25°C to +55°C
Operating Humidity	⩽95% RH, non-condensing
Product Dimensions	160 × 223 × 146 mm
Package Dimensions	185 × 155 × 245 mm
Product Weight	2.11 kg
Warranty	2 years

DIMENSION

NAC-710W	WEIGHT	MM
PRODUCT DESCRIPTION	OUTER DIMENSIONS (W*H*D)	UNIT HEIGHT
WALL SPEAKER	160 × 220 × 146 mm	N/A

