GEN-5501P70 Network Multi-Zone Amplifier





SIP Onvif Multicast 6-Zones

INTRODUCTION

SPON Netwrok Multi-Zone Amplifier GEN-5501P70 is an AC-powered network 6-zone amplifier with a built-in Class-D digital amplifier, supporting 70V/100V constant-voltage output. It can receive SIP calls from telephones or VMS platforms, handle up to 20 multicast streams, and store up to 20 audio files. In addition, it features priority management, timer scheduling, Bluetooth connectivity, and custom actions triggered via HTTP API, enabling independent control of six broadcast zones for schools, shopping malls, campuses, and various indoor zoned public address applications.

MAIN FEATURES

- **6-Zone Paging:** Supports six broadcast zones to meet the needs of multi-area paging and zoned audio management.
- **Independent Zone Control:** Enables independent control and switching of different areas, suitable for schools, shopping malls, campuses, and other zoned public address applications.
- **Built-in Digital Amplifier:** Features a built-in Class-D digital amplifier with 70V/100V constant-voltage output, including overload and overheat protection.
- **Multiple Audio Inputs:** Provides two line inputs, one balanced microphone input, and Bluetooth audio input for flexible source connection.
- **Network Broadcasting Capability:** Supports up to 20 multicast audio streams and can receive SIP calls for network audio broadcasting.


PARAMETERS:

Network Interface	100BASE-TX, RJ45 Connector
Network Protocols	TCP/IP, UDP, HTTP, RTP, RTSP, ARP, ICMP, NTP, SIP, ONVIF, DHCP
Configuration	Web Interface or DevConfig Tool
Audio Transmission	Multicast, up to 20 streams (editable)
Audio Codec	Opus, PCMU (G.711u), PCMA (G.711a), G.722
Audio File Format	WAV, MP3
Audio Storage	Max 20 audio files, 80 MB
Audio Stream	WAV: 8/16/22/44.1/48 kHz sampling rate, 8/16-bit, mono/stereo; MP3: 32/44.1/48 kHz sampling rate, 64–320 kbps, CBR/VBR, mono/stereo
SNR	⩾85 dB
Frequency Response	130 Hz to 18 kHz (±3 dB)
THD+N	<0.1%@1 kHz
Amplifier Type	Class-D
Audio Input Connectors	Line In 1: 1 × 3-Pin Phoenix Connector, Balanced, 500 mV; Line In 2: 1 × 3-Pin Phoenix Connector, Balanced, 500 mV; Mic In: 1 × 6.5 mm TRS, Balanced, 25 mV; Bluetooth: 1 × IPX1 External 2.4G Antenna; Network: 1 × RJ45 Connector
Audio Output Connectors	1 × 4-Pin Phoenix Connector (Power Output); 2 × RCA Jacks (AUX Output)
Audio Output Power	70V/100V: 1 × 700 W
Number of Physical Zones	6, supports independent control of 6 broadcast zones
Input Voltage	180V~240VAC, 50/60Hz
Standby Power Consumption	<10 W
Maximum Power Consumption	<800 W
USB:	USB 2.0
Control Input	2, 1 × 3-Pin Phoenix Connector
Control Output	1, 1 × 3-Pin Phoenix Connector
EMC Out	1, DC24V/2A
Accessory (Reserved)	1
Housing Material	Sheet Metal
Color	Gray + Black
Mounting	Desktop, Wall-mounted, Rack-mounted
Application Environment	Indoor
Operating Temperature	0°C to +50°C
Operating Humidity	⩽90% RH, non-condensing
Dimensions	483 × 317 × 44 mm
Package Dimensions	573 × 368 × 123 mm
Net Weight	4.4 kg
Warranty	2 years

ACCESSORIES:


ACCESSORIES	1 × Power Cord (Optional) 1 × 2.4G Rod Antenna 8 × Countersunk Phillips Screw (M3×6) 4 × Foot Pad (FF-7) 2 × Wiring Terminal (3.81mm, 6-pin) 1 × Wiring Terminal (7.62mm, 4-pin) 2 × Hanger 1 × Wiring Terminal (3.81mm, 2-pin)

CONNECTION DIAGRAM




APPLICATION 1

The GEN-5501P70 Network Multi-Zone Amplifier receives audio streams through protocols such as SIP, ONVIF, and multicast, and outputs audio to analog amplifiers or constant-voltage speakers. It supports multiple local audio inputs (microphone, line input, Bluetooth, and USB) for local broadcasting and background music. With a built-in Class-D digital amplifier that offers high efficiency and low heat generation, it is ideal for public address system setups.



DIMENSION


317
483
465
49
44
32
305
GEN-5501P70
PRODUCT DESCRIPTION
NETWORK MULTI-ZONE AMPLIFIER
OUTER DIMENSIONS (W*H*D)
483 x 317 x 44 mm
UNIT HEIGHT
N/A
WEIGHT
4.4 kg
MM